

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Arcos Nufive  
Application: Arc Welding  
Classification(s): EN 499: E 38 2 C 11  
SFA/AWS A5.1: E6011  
Supplier: ESAB AB, Box 8004  
402 77 Göteborg, Sweden  
Telephone no.: +46 31 509000

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a preparation of core wire with extruded coating. The core wire type is mild steel.

Coating Ingredients	Weight % less than	CAS#	EINECS#	Hazard classification <sup>(1)</sup>	TLV <sup>(2)</sup> mg/m <sup>3</sup>
Cellulose	30	9004-34-6	232-674-9	No	10
Iron	2	7439-89-6	231-096-4	No	5
Limestone	10	1317-65-3	215-279-6	No	10
Manganese	10	7439-96-5	231-105-1	No	0.2
Potassium oxide	5	12136-45-7	235-227-6	No	-
Silica gel	25	7631-86-9	231-545-4	No	10
Sodium oxide	5	1313-59-3	215-208-9	No	-
Titanium oxide	25	13463-67-7	236-675-5	No	10

<sup>(1)</sup> Hazard Classification acc. to EC Directive 67/548/EEC, for R-phrases see heading 16.

<sup>(2)</sup> Threshold Limit Values according to ACGIH 2004

## 3. HAZARDS IDENTIFICATION

Avoid eye contact or inhalation of dust from the product. Skin contact is normally no hazard but should be avoided to prevent possible allergic reactions.

When this product is used in a welding process, the most important hazards are heat, radiation, electric shock and welding fumes.

Heat: Spatter and melting metal can cause burn injuries and start fires.

Radiation: Arc rays can severely damage eyes or skin.

Electricity: Electric shock can kill.

Fumes: Overexposure to welding fumes may result in symptoms like dizziness, nausea, dryness or irritation of the nose, throat or eyes. Chronic overexposure to welding fumes may affect pulmonary function. This product contains substances that may affect the nervous system.

## 4. FIRST AID MEASURES

Inhalation: If breathing is difficult, provide fresh air and call physician.

Eye contact: For radiation burns due to arc flash, see physician.

Skin contact: For skin burns from arc radiation, see physician.

General: Move to fresh air and call for medical aid.

## 5. FIRE FIGHTING MEASURES

No specific for welding consumables.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: refer to section 8

Environmental precautions: refer to section 13

## 7. HANDLING AND STORAGE

Handling:

Avoid exposure to welding fumes, radiation, spatter, electric shock, heated materials and dust. Do not ingest. Handle with care to avoid stings and cuts.

Storage:

Keep separate from chemical substances like acids and strong bases, which could cause chemical reactions.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures:

Ensure sufficient ventilation and exhaust at the arc to keep the welding fumes and gases away from welders breathing zone. Keep working place and protective clothing clean and dry. Train welders to avoid contact with live electrical parts and insulate conductive parts. Check condition of protective clothing and equipment on a regular basis.

Personal protective equipment:

Use respirator or air supplied respirator when welding - brazing in a confined space. Wear hand, head, eyes and body protection like welders gloves, helmet or face shield with filter lens, safety boots, apron, arm and shoulder protection. Keep protective clothing clean and dry. Persons with a pacemaker should not go near welding or cutting operations until they have consulted their doctor and obtained information from the manufacturer of the device.

Threshold Limit Values according to ACGIH: refer to section 2

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Solid, non-volatile with varying colour

Melting point: >1300°C

## 10. STABILITY AND REACTIVITY

General: This product is only intended for normal welding purposes.

Stability: This product is stable under normal conditions.

Reactivity: Contact with chemical substances like acids or strong bases could cause generation of gas.

When this product is used in a welding process, hazardous decomposition products would include those from the volatilization, reaction or oxidation of the materials listed in section 2 and those from the base metal and coating.

The amount of fumes generated from this product, varies with welding parameters and dimensions.

Fume analysis: Fe Mn Pb Cu Ni Cr  
weight % less than 55 10 0.1 0.1 0.1 0.1

Reasonably expected gaseous products would include carbon oxides, nitrogen oxides and ozone.

## 11. TOXICOLOGICAL INFORMATION

Inhalation of welding fumes and gases can be dangerous to your health. Classification of welding fumes is difficult because of varying base materials, coatings, air contamination and processes.

Acute toxicity: Overexposure to welding fumes may result in symptoms like metal fume fever, dizziness, nausea, dryness or irritation of the nose, throat or eyes.

Chronic toxicity: Overexposure to welding fumes may affect pulmonary function. Overexposure to manganese may affect the nervous system.

## 12. ECOLOGICAL INFORMATION

Welding consumables and materials could degrade/weather into components originating from the consumables or from the materials used in the welding process. Avoid exposure to conditions that could lead to accumulation in soils or groundwater.

## 13. DISPOSAL CONSIDERATIONS

Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal and local regulations. Use recycling procedures if available.

Residues from welding consumables and processes could degrade and accumulate in soils and groundwater.

## 14. TRANSPORT INFORMATION

No international regulations or restrictions are applicable.

## 15. REGULATORY INFORMATION

Read and understand the manufacturer's instructions, your employer's safety practices and the health and safety instructions on the label. Observe any federal and local regulations. Take precautions when welding and protect yourself and others.

FUMES AND GASES can be dangerous to your health.

ARC RAYS can injure eyes and burn skin.

ELECTRIC SHOCK can kill.

WARNING: Avoid breathing welding fumes and gases, since they may be hazardous to your health. Use adequate ventilation. Arc rays may injure eyes and burn skin. Wear correct eye, ear and body protection. Do not touch live electrical parts.

## 16. OTHER INFORMATION

Refer to ESAB "Welding and Cutting - Risks and Measures" Reg.No.XA00096120, available from ESAB and to:

USA: American National Standard Z49.1 "Safety in Welding and Cutting", American Welding Society, 550 North Le Jeune Road, Miami, Florida, 33135; OSHA Safety and Health Standards, 29CFR 1910, U.S Gov.Printing Office, Washington, D.C. 20402; American Conference of Governmental Hygienists (ACGIH), Threshold Limit Values and Biological Exposure Indices, 6500 Glenway Ave., Cincinnati, Ohio 45211, USA.

UK: WMA Publication 236 and 237, "Hazards from Welding fume", "The arc welder at work, some general aspects of health and safety".

Germany: Unfallverhütungsvorschrift BGV D1, "Schweißen, Schneiden und verwandte Verfahren".

ESAB request the users of this product to study this Safety Data Sheet (S.D.S.) and become aware of product hazards and safety information. To promote safe use of this product a user should:

- notify its employees, agents and contractors of the information on this S.D.S and any product hazards/safety information.
- furnish this same information to each of its customers for the product.
- request such customers to notify employees and customers for the same product hazards and safety information.

The information herein is given in good faith and based on technical data that ESAB believes to be reliable. Since the conditions of use is outside our control, we assume no liability in connection with any use of this information and no warranty, expressed or implied is given. Contact ESAB for more information.