

## Mobiflex 200-M Base Unit

### Low Vacuum Base Unit

Product Number: 7028100700

Lincoln's ProSource LV low vacuum fume extraction products combine the finest features in the industry with the best value.

The Mobiflex 200-M provides mobile fume extraction with either a 3 or 4 metre Deblock, or spring balanced extraction arm. By using durable, dent-resistant thermoplastic tubes, the lightweight arms position easily and hold their place without drifting. The Mobiflex 200-M draws air through the self-cleaning fan and spark arrestor and captures welding fume inside the unique LongLife filter. Lincoln's 50 Sq.Mtr. LongLife filter, with its ExtraCoat surface treatment and 3-dimensional pleating, is the largest single cartridge found in any mobile welding fume unit currently on the market. In some cases it has twice the filter area of competitors equipment.

The Mobiflex 200-M also features a filter maintenance indicator. This shows ahead of time how close the filter is to clogging.

### Advantage Lincoln

- Provides 1,200CuMtr/Hr airflow.
- 50Sq.Mtr. surface treated filter cartridge included.
- Quiet operation: 69dBA.
- Filtration efficiency of 99.8%.
- Maintenance indicator gauges the amount of dust build-up in the filter.
- Includes aluminum spark arrestor.
- Optional work lamp provides lamp and hood mounted switches for both lamp and fan.
- Recommended for annual Solid MIG wire use of less than 700Kg. per station (500Kg. for SMAW or FCAW).

### Physical specifications

Weight: 111 kgs.

Dimensions (mm) H x W x D : 900 x 810 x 1210



### Recommended Options

- [7925170180](#) LFA 3.1 - 3 metre Extraction Arm
- [7925160180](#) LFA 3.0 - 3 metre Extraction Arm
- [7900010140](#) Working light
- [9820300040](#) Transformer/relay kit
- [7900010150](#) Automatic start/stop

### Specifications

Input - Voltage/Phase/Hertz	Airflow Rating
115/1/50Hz	1 200CuMtr/Hr